



Foreword

Viega is committed to sustainable actions that uphold the very highest standards. Our suppliers play a major role in ensuring that we grow sustainably and achieve successful results.

These delivery regulations outline the minimum requirements for transport containers, load carriers, packaging and labelling, plus the delivery documents that need to be provided.

These delivery regulations apply subject to any individual agreements that deviate from them or any other regulations that apply to all plant/logistics deliveries on the basis of individual contracts.

If there is a failure to comply with the regulations outlined here, Viega reserves the right – at its own discretion – to refuse acceptance of the goods or to repackage the goods at the supplier's expense.

If any specific passages in these delivery and packaging regulations need clarification or there are questions about them, please contact those responsible for incoming goods at the delivery address before making the delivery.



Contents

1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information



Contents

1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information

Notification



All deliveries containing 5 or more loading units must be announced at least 24 hours in advance, with the notification sent during working hours.

General delivery information



Procedure when delivering

- Registration at the gate
- Then registration at the incoming goods area with accompanying documents
- Those responsible for incoming goods grant approval to use certain doors, etc.

Goods deliveries (completeness)

 The supplier must ensure that the goods are delivered in full

Viega specifications

- All deliveries must comply with Viega specifications, including the following:
 - Only load carriers and containers that align with Viega's specifications (article master list) may be used
 - Boxed goods must be delivered in line with Viega's specifications (article master list). This includes the use of neutral packaging (no third-party company logos, labelling on packaging boxes, etc.)

General delivery information



Communication

 All persons making deliveries must be able to communicate in German or English.

Sprinter or side unloading

Unloading from the side or rear of a Sprinter van must be announced at least 24 hours in advance, with the notification sent during working hours with the explicit note "Sprinter or side unloading". SHö/LHe | September 2023

Vehicle preparation

 The driver must prepare the vehicle in line with VDI 2700, ensuring that it can be loaded and unloaded quickly and safely whenever required.

Returns

 Return goods must have clearly visible labelling.

Access to goods

 The goods must be freely accessible. Viega employees are not permitted to move thirdparty goods.

Load carrier exchange

 After an immediate incoming goods inspection, Viega reserves the right to refrain from exchanging defective load carriers or to document damage sustained in transit.



Contents

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information

Goods slip

Requirements for <u>internal Viega</u> deliveries

- Load carriers being forwarded internally must be accompanied by an attached, fully completed and clearly visible goods slip.
- The goods slip version that is currently valid must be used.
- If goods, load carriers or similar are being collected, the collector must always remove the accompanying goods slip.

an Werk:		Logistik				
Abteilung: z.Hd.:		SpD Allgemein				
		Max Mustermann		Tel.:		
Fert. Org.	Nr.:				230111	
	- 100					
			Spedition, GLS oder UPS verschick	werden. Gil	t nicht für Werkstransporte	
Angabe der Vie	ga-Orga	inisation:		100000	Maddid I	
Angabe der Ver Projekt- oder Be					the Bury II	
Projekt- oder Be	stellnu	mmer:				
Anzahl Ver	rsand	leinheiten:		N told		
Europaletten:	1	Gitterboxen:	Schäferbehälter:		Rohrbunde:	
KLT's:		Kartons:		1860		
IN STATE OF	Ren ·	Ware wird am 22.03.2	2021 abreholt	11-18		
Anmerkung:	Sec. Print	Truit Hill alli EE.00.2				
Anmerkung:	ME					
Anmerkung: Liefertermin an l	Empfän	ger:				
	Empfän	ger:				
	Empfän	ger:				
lefertermin an i		ger:				
	ilung:			Tel.:		

Markus Heliner

Ricarda Troster

Accompanying documents



The following documents are required:

- Delivery note ¹
- Freight documents (CMR, shipping transfer note, etc.)
- Packing list, etc.
- Test report according to DIN EN 10204:2005-01²
- Visitor's pass form for the location in question
- Old labels or shipping documents must be removed or provided with the goods in a separate envelope

1) Can also be provided via email

²⁾ Must be provided via email at least 1 day before the delivery Email: werkszeugnisse@viega.de





Required content

- Supplier's contact details
- Exact delivery address and unloading point
- Delivery note number
- Name of freight forwarder
- Viega order number
- Date of order
- Item number according to SAP order
- Viega material number (e.g. 00505163)
- Viega article designation
- Batch number (if available)
- Drawing number with index
- Quantity/load carrier

- Total quantity
- Number of load carriers/units
- Weight specifications: gross and net weight
- Delivery notes must be attached to the goods in a clearly identifiable location
- The number of loading units must be specified on the delivery note

The information on the delivery documents must match the information on the loading units.

Customs invoice

General information

- Goods must already have customs paid on them when they are delivered to Viega.
- Before the goods are unloaded, the documents must be presented and evidence that customs have been correctly paid on the goods must be provided.
- Without being prompted to do so, the person making delivery must present the customs documents (T1 document) or CMR consignment note confirming customs clearance.

Example of a CRM with a customs stamp Contract Services 24 CITE BRIDGE (Downless (MI)) Strategie Strate Charles Smith Sa. 100 on last or discharge Contractor S Mathematica de la magintipatica Projetty Special Right Rundershirehre mit knendungt FIRMS DODGE SWILL BY Rentaliant street and improbate TRUG MICH HYDRON, PW glamps, P. emburges are Absorbery (Adv. and sorolige arcite/se forwesturg): 27 21 0000 A MARKAGES 23 Vinel Transporte Gold. A CARS Bladwid Car



Customs invoice

Typical examples of customs clearance documents include the following in particular:

- Export declaration
- Commercial invoice
- Or, in the case of e.g. consignment deliveries or free samples, a pro-forma invoice
- Packing list
- Packing declaration
- Certificate of non-preferential origin or proof of preferential origin, as specified in the applicable free trade agreement







1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information





General requirements:

- Goods must be sorted according to type in their deliveries
- The following applies if individual agreements with deviating requirements are in place:
 - Mixed pallets must be clearly labelled and the packing list etc. supplied
 - Boxes with residual quantities must be labelled when closed with a total of 3 labels (at the top and at the side and face ends)
 - All 3 residual quantity labels must be positioned so that they are clearly visible
 - Number of pieces per loading unit and box





Load carrier labelling

Example: pallet cage with goods for production

- Each load carrier must have an appropriate container label
- This can be a label generated by the supplier or a load carrier label that complies with VDA 4902 or VDA 4994
- Load carrier labels must show the following information as a minimum:
 - Viega material number
 - Viega material number in the form of a barcode (Code 39, Code 128 or DataMatrix code)
 - Drawing number + index
 - Batch number
 - Quantity
 - Material ID card for steel & stainless steel components









Load carrier labelling (pallet cage example)

Example of pallet cage with goods for production

Supplier data

Article no. 240071


Drawing number: 60092 S

Batch: QW XY

Quantity: 4500 pieces









Load carrier labelling

Example of Europallet with goods for production

Supplier data

Article number 240071

Drawing number: 60092 S

Batch: QW XY

Quantity: 4500 pieces









Positioning of Viega material card

The following applies when using Viega material cards:

- All information on the material card must be clearly visible and scannable. The material card must show the following information:
 - Quantity per loading unit
 - Date and signature
 - Material number barcode
- The material card must be attached to the loading unit in a clearly visible position, must not be attached across multiple boxes and must not flap around loosely
- Pallets > 1 m high: one material card on each of the long sides
- Pallets < 1 m high: one material card at the top of the goods
- Box barcodes or similar must not be covered
- Do not staple the material card to packaging bags containing bulk materials













Other forms of labelling

Special labels


 Special labels and notes (e.g. "Backordered articles" or "To be forwarded to...") must be attached in a place that is clearly visible





Deliveries from third countries

 In the case of deliveries from third countries, there must be clearly identifiable information that customs have been paid on the goods





Dangerous goods

Dangerous goods must be labelled in accordance with the existing laws, directives and standards!



Contents

1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information



Europallet

Requirements 1/3

- EPAL standard in accordance with DIN 15146-2 (see also www.gpa
 - Max. permitted gross weight: 800 kg
 - Only new, light-coloured pallets may be used
 - Dimensions (incl. load carriers):

	Height class 1	Height class 2
Length	1200 mm	1200 mm
Width	800 mm	800 mm
Height	950 mm	1950 mm

- Items loaded on pallets must not sag or protrude. Pallet dimensions must be strictly adhered to
- It must be possible to transport/stack/warehouse/convey the pallets at any given time



Source: www.gpal.de



Europallet

Requirements 2/3

- All of the pallet feet must be easily visible and must not be soiled (film must not be wound around the feet, they must not be dark, etc.)
- Plastic strapping must be used
- 4 straps must be attached in the case of height class 2
- The straps must not be twisted
- Stretch wrap or shrinkwrap is only permitted as a way of protecting against soiling or moisture, not as a way of securing goods to the pallet. The exception is goods that cannot be secured with other standard methods
- When stretch wrap is being used, the wrap must be wound fully around the top pallet board and the wrap ends secured to the long side











24

Europallet

Requirements 3/3

- If small load carriers (SLC) are being delivered on a pallet, a complete layer must always be formed (4, 8, 12, etc. SLC per pallet).
- Complete layers are desirable in deliveries of boxes on pallets.
- Goods packed in boxes must not be stacked.
- If a layer is incomplete, the last complete layer must be bound and the remaining quantity placed on top of it in boxes. All boxes must be secured appropriately.














Pallet cages

Requirements 1/2

- EPAL standard in accordance with DIN 15155 (see also www.gpal.de)
 - Max. permitted gross weight: 850 kg
 - New pallet cages must be used
 - Dimensions (incl. load carriers):

	Height class 1
Length	1200 mm
Width	800 mm
Height	950 mm

- The packaging and its contents must not extend above the top edge of the cage or protrude at the sides.
- It must be possible to transport/stack/warehouse/convey the pallet cages at any given time





Pallet cages

Requirements 2/2

- Flaps must be closed. They must not be secured with cable ties or any other means
- Delivery notes and other accompanying documents must not be attached to pallet cages, as cages may be warehoused
- If bulk materials are being supplied in a side fold bag, a covering piece of cardboard must be used
- Pallet cages must not have film wound around them
- There must not be any paper, labels, etc. on the short ends or sides
- The feet of the pallet cage must not be soiled (black colour, rusty, etc.)







One-way pallets

- All the same requirements as those for Europallets apply, with the following exceptions:
 - Dimensions (incl. load carriers):

	Height class 1	Height class 2
Length	1200 mm	1200 mm
Width	800 mm	800 mm
Height	800 mm	1800 mm

 Deliveries on one-way pallets are not desirable and are only permitted if agreed

Schäfer containers

- Only use Schäfer containers labelled "Franz Viegener II, Attendorn"
- Max. permitted gross weight: 800 kg
 - Dimensions (incl. load carriers):

	Height class 1
Length	1200 mm
Width	800 mm
Height	950 mm

- The packaging and its contents must not extend above the top edge of the container
- Schäfer containers must not have film wound around them
- Flaps must be closed

SHö/LHe | September 2023 27

Other load carrier requirements



Iron crates

Deliveries in iron crates are not permitted

Wire baskets

- All the same requirements as those for Europallets apply, with the following exceptions:
 - Max. permitted gross weight: 500 kg
- Wire baskets must be stacked in a maximum of 2 layers on pallets and must be secured firmly







1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information



Container types

SLC containers

- Max. permitted gross weight: 35 kg
- Strapping and edge protection required; no film wound around the containers





Automated small-parts warehouse (ASW) containers

- Max. permitted gross weight: 35 kg
- Strapping and edge protection required; no film wound around the containers






Using more than one container type on the same pallet is not permitted.



Dimensions and specifications

Barcode dimensions



Barcode specifications

Interleaved 2 of 5

10 digits

NBW: 0.498 mm

Ratio: 3:1

• Quiet zone:

5 mm (minimum)

Bar length: 50 mm

Orientation: ladder


- ISO/IEC 15416

Barcode orientation with text on right

SHö/LHe | September 2023 3²



Barcode positions




Barcodes on warehouse containers are positioned

- 60 [mm] from the underside of the warehouse container up to the middle of the code and
- 80 [mm] from the front edge of the warehouse container up to the middle of the code
- on both long sides (left front/rear right)
- The warehouse container does not have any subdivisions



Tolerances



The maximum tolerance for barcodes (on manually applied adhesive labels) is +/-5 mm in height with a maximum rotation of 10°.



Container types: SLC containers and ASW containers Number range

The following number ranges are specified for manually attaching to containers:

052xxxxxxx: old ASW containers

056xxxxxxx: production SLC containers

Barcodes must be requested from Manuela Wittmann if required

Contact:

manuela.wittmann@viega.de

Suppliers are not permitted to use container types that are their own and have not been provided by Viega.



Example



80 mm



60 mm





1

General delivery information

2

Delivery documents

3

Labelling

4

Load carriers

5

Container types

6

Other information

Other information



Box

- All boxes must be delivered in line with Viega's specifications (article master list)
- A maximum of 1 box containing a remaining quantity/partial quantity is permitted per delivery

Labels/barcodes

- All boxes must be delivered in line with Viega's specifications (article master list)
- A maximum of 1 box containing a remaining quantity/partial quantity is permitted per delivery

Packing pattern/layer formation

 The packing pattern/layer formation must comply with Viega's specifications

Questions on any specifications must be clarified with the contact person in advance. The contact details can be found in the order information, for example.

Copyright



This presentation or parts thereof may be subject to brand or copyright protection. Viega GmbH & Co. KG retains exclusive usage rights.

Unauthorised use, copying in full or in part or dissemination to third parties is not permitted.

info@viega.de viega.de

All contents in this document have been compiled with the greatest possible care and attention. Despite this, we are unable to guarantee that the information is up to date, accurate and complete, or that the website can be accessed without problems at all times. Viega accepts no responsibility for the content of references and links to third-party websites. Liability for damage arising from slightly negligent breaches of duty is excluded if it does not affect material contractual duties and does not involve injuries to life, limb or health.